




Flamehawk® Flame Detector

Forney's FlameHawk® fiber optic flame detector is a dual channel solid-state device designed for industrial and marine gas turbines.



www.forneycorp.com

PRODUCT OVERVIEW

The FlameHawk® fiber optic flame detector is a dual channel solid-state device designed for direct replacement of Geiger-Mueller (GM) tube flame sensors used on industrial and marine gas turbine engines.

The FlameHawk® flame detector improves performance and reduces maintenance costs. It has durable fiber optic cables that transmit the spectral energy from the combustion process to the electronics module. This allows for remote mounting of the electronics outside of the engine enclosure, which eliminates complicated and costly cooling systems common in other flame sensors.

The FlameHawk® flame detector system works in low NOx combustors, multiple fuel applications and with systems incorporating steam injection.

Operational Principles

The fiber optic cables and optical probes offer easy installation and maintainability. Simple threaded connections are used throughout the system to allow for rapid installation without the need for special tooling. Unique features, such as a quick-release clamp on the frame engine optical probe, have been incorporated to ease cleaning and inspection.



FEATURES & BENEFITS

- Mechanically and electronically interchangeable with other flame sensors.
- Remote mounting of electronics.
- Optical probe mounts directly to engine.
- No external cooling required.
- Dual channel – easy installation and less wiring.
- Multiple fiber optic cable lengths available.
- Quick disconnect clamp allows for easy cleaning of adapter lens.
- Low voltage operation.
- Multiple field configurable outputs: relay, 4-20 mA, 4-20 mA loop.
- Signal strength meter provides visual indication of system health.
- Reliable operation when using gas or liquid fuel.
- Proven operation in steam injection applications.
- Industrial boiler flame, auto-ignition and flashback detection.


FlameHawk® Flame Detector

Model 705 Series

Products and Accessories:

00705-0225-0007	Amplifier, with Connector	00705-0192-0120	10' (3.05m) F/O Light Guide Top Assembly
00705-0225-0008	Amplifier, without Connector	00705-0192-0180	15' (4.57m) F/O Light Guide Top Assembly
00705-0225-0009	Amplifier, ATEX, IECEx Approved	00705-0192-0300	25' (7.62m) F/O Light Guide Top Assembly
00705-0185-0001	Aeroderivative Sight Tube, Inconel/Sapphire	00705-0192-0480	40' (12.2m) F/O Light Guide Top Assembly
00705-0212-0001	Coupling Mounted Frame Application Sight Tube, 316 SST, Quartz	00705-0258-0001	Replacement Quartz Lens Assembly
00705-0239-0001	Flange Mounted Frame Application Sight Tube, 316 SST, Quartz		
00705-0242-0001	Interface cable to 00705-0225-0007		

General Specifications

Electronics Module Performance		
Sensitivity:	Calibrated with 1μW radiance (@ 370 nm) Correlates to Relay Switch Point or 7.0 mA	
Response Time (On / Off)	Less than 50 milliseconds	
Electrical		
4-20 mA and Relay Using Signal Strength Meter	18 to 32 VDC @ > 50 mA, 4-20 mA and relay. May be operated simultaneously	
4-20 mA Max. Load	<650 ohms at 18 VDC to 1350 ohms at 32 VDC (linear)	
4-20 mA Loop Powered	18 to 32 VDC with 4 mA headroom	
Relay Rating	Resistive: 1A @ 30 VDC Load: 0.5A @ 125 VDC	
Mechanical		
Enclosure Material	Aluminum	
Optical Interface	Female 3/8" compression-style fitting	
Electrical Interface	Standard versions - 3/4" NPT conduit hole. ATEX/IECEX version - MS38999/20WD97PN conduit hole for ATEX gland.	
Enclosure Mounting	11 mm (0.437 inch) diameter holes (2x)	
Weight	6.8 lbs (3.1 kg)	
Enclosure Certifications	Class I, Div. 1 & 2, Groups B, C & D NEMA 3, 4, 4X, 7 (B, C, D), 9 (E, F, G) CENELEC – EEx d IIC, T6 or T5	
ATEX/ IECEX certification #:	FM16ATEX0035X/ IECEX FMG 16.0025X	
Environmental		
Operating Temperature	-22°F to 158°F (-30°C to 70°C)	
Vibration	8g over a range of 5 to 1200Hz	
Humidity	0 to 100% relative humidity	
Agency Approvals		
ATEX/IECEX version Part #00705-0225-0009	 II 3 G	Ex db ec IIB + H2 T6 Gc -30°C < T _{AMB} < +70°C

Fiber Optic Cables

Mechanical	
External Sheath Material	316 Stainless steel (dual layer)
Fiber Material	Fused silica – UV enhanced
Optical Interface Probe	3/8" compression-style fitting
Bend Radius	4" (101.6 mm) minimum
Environmental	
Temperature Range	-40°F to 662°F (-40°C to 350°C)

Optical Probe - Aeroderivative

Mechanical	
Material	Inconel 625
Engine Interface	5/8-18 UNF external thread
Fiber Optic Interface	3/8" compression-style fitting
Window Material	Sapphire
Environmental	
Temperature Range	-40°F to 1095°F (-40°C to 590°C)
Maximum Pressure	6895 kPa (1000 psi)

Optical Probe - Frame

Mechanical	
Material	316 stainless steel
Engine Interface	3/4" NPT external thread or flange mount
Fiber Optic Interface	3/8" compression-style fitting
Window Material	Quartz
Purge Port	1/8" NPT (if needed)
Environmental	
Temperature Range	-40°F to 572°F (-40°C to 300°C)
Maximum Pressure	4137 kPa (600 psi)